



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R404A / R507**

Specifications	MONIKA 2/1.0	MONIKA 2/1.3	MONIKA 2/1.5	MONIKA 2/1.7	MONIKA 2/2.05	MONIKA 2/2.5
CODE	MO100	MO101	MO102	MO103	MO104	MO105
Length [mm]	1070	1310	1510	1710	2050	2520
Length with the sides [mm]	1060	1300	1500	1700	2040	2520
Capacity [dm ³]	160	210	240	270	330	410
Working capacity of the chamber [dm ³]	160	210	240	270	330	410
The area of shelves [m ²]	0,5	0,6	0,7	0,8	1	1,25
Cooling area of shelves [m ²]	0,5	0,6	0,7	0,8	1	1,25
Side panel thickness [mm]	40	40	40	40	40	40
Depth [mm]	830	830	830	830	830	830
Height [mm]	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10	1220+/-10
Unit weight [kg]	110	130	150	170	190	220
Refrigerant/Cooling factor	R134a	R134a	R134a	R134a	R134a	R404A / R507
Evaporating temperature [°C]	-15	-15	-15	-15	-15	-15
Cooling power demand [W/mb]	300	300	300	300	300	300
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz
Rated power of lighting [W]	14,4	14,4	17	22,4	22,4	34
Rated power [W]	286,4	286,4	290	365,4	365,4	450
Cooling power [W]	412	412	412	549	549	605
Electricity consumption [kWh/24h]	4	4	4,1	5,1	5,1	6,3
Shelf load [kg/m]	50	50	50	50	50	50

Standard equipment

internal cooling aggregate

static cooling

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of white coated steel

storage chamber made of white coated steel

storage chamber back doors - hinged

worktop - stainless steel

anodised aluminum profiles color gold or silver (IGLOO pattern book)

curved front glass openable

LED lamp (color of choice: white, confectionery or meaty "deep pink")

bumper - different colors available (IGLOO pattern book)

insulated plastic side walls + glass side panels - different colors available (IGLOO pattern book)

automatic defrost

condenser outlet to container

electronic temperature controller with digital display (IGLOO)

condenser impurity or fan operation failure alarm

Options

housing with base panel from staff side made of stainless steel

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

front panel color - different colors available (IGLOO pattern book)

custom front panel color (after consultation with the IGLOO Sales Department)

base panel made of stainless steel

exposition area made of stainless steel

storage chamber made of stainless steel

exposition area made of acid resistant stainless steel

storage chamber made of acid - resistant stainless steel

powder painted evaporator

night blinds made of plexi glass

worktop - granite grey (thickness : 20 mm)

worktop - granite Balmoral (thickness : 20 mm)

worktop - granite black (thickness : 20 mm)

additional exposition glass shelf

delivery overlay for the stainless steel panel front window

set of wheels (castors)

additional LED light in top lamp profile

automatic defrost

the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)

automatic condenser vaporization

analog thermometer

electronic temperature recorder + software

recorder cable

socket with fuse

customer front shelf (aluminum profile anodised color silver or gold)

movable partition (low ,glass on stands , placed in exposition area)

top fixed partiton (high , glass in exposition area)

bottom fixed partition (made from stainless steel in storage chamber)

runner for small movable table

small movable table for scale or cash register (400x500mm)

