



Temperature range: **+1°C/+10°C**

Refrigerating unit: **Internal**

Refrigerant/Cooling factor: **R290 / R449**

Specifications	BASIA NEO 0.94	BASIA NEO 1.25	BASIA NEO 1.56	BASIA NEO 1.88	BASIA NEO 2.50	BASIA NEO 3.13	BASIA NEO 3.75	BASIA NEO NW90	BASIA NEO NZ90
CODE	BN120	BN130	BN140	BN150	BN160	BN170	BN180	BN190	BN195W
Length [mm]	938	1250	1563	1875	2500	3125	3750	-	-
Capacity [dm3]	115	155	193	233	310	388	465	-	-
Exhibition area [m2]	0,9	1,2	1,2	1,8	2,4	3,0	3,6	-	-
Depth [mm]	1155	1155	1155	1155	1155	1155	1155	1155	
Height [mm]	1220±10	1220±10	1220±10	1220±10	1220±10	1220±10	1220±10	1220±10	
Refrigerant	R290	R290	R290	R290	R290	R449	R449	R134a	R134a
Evaporating temperature [°C]	-15	-15	-15	-15	-15	-15	-15	-15	
Cooling power demand [W/mb]	350	350	350	350	350	350	350	350	
Rated voltage [V]	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	230/50Hz	
Rated power of lighting [W]	24	32	39	47	63	79	94	32	-
Rated power [W]	354	382	389	467	533	1179	1194	382	-
Cooling power [W]	479	564	564	654	730	1200	1300	-	-
Electricity consumption [kWh/24h]	5,0	5,3	5,4	6,5	7,5	16,5	16,7	5,3	-

## Standard equipment

internal cooling aggregate

insulated plastic sides + glass sides - selectable colour (IGLOO colour chart)

static cooling

body with service - side base flashing composed of white, coated sheet metal

front base sheets and front panel with color-coated sheet - selectable color (IGLOO color guide)

ecological polyurethane foam insulation

exposition area made of stainless steel

storage chamber made of white coated steel

storage chamber back doors - hinged (not applicable to corners)

worktop – stainless steel

---

anodised aluminum profiles color gold or silver (IGLOO pattern book)

---

curved front glass openable

---

LED lamp (color of choice: white, confectionery or meaty “deep pink”)

---

bumper - different colors available (IGLOO pattern book)

---

insulated plastic side walls + glass side panels – different colors available (IGLOO pattern book)

---

automatic defrost

---

condenser outlet to container

---

analog thermometer

---

electronic temperature controller with digital display (IGLOO)

---

condenser impurity or fan operation failure alarm

---

## Options

device prepared for multiplexing

---

device without side panels prepared for multiplexing (MOD/A)

---

housing with base panel from staff side made of stainless steel

---

front panel color different than IGLOO pattern book (please contact IGLOO sales dept.)

---

front panel color – different colors available (IGLOO pattern book)

---

custom front panel color (after consultation with the IGLOO Sales Department)

---

base panel made of stainless steel

---

display space with coloured sheet - selectable colour (IGLOO colour chart)

---

storage chamber made of stainless steel

---

exposition area made of acid resistant stainless steel

---

storage chamber made of acid – resistant stainless steel

---

exposition area – stepped – 2 steps

---

exposition area – stepped – 3 steps

---

powder painted evaporator

---

night blinds made of plexi glass

---

worktop - granite grey (thickness - 20 mm)

---

worktop - granite Balmoral (thickness : 20 mm)

---

worktop – granite black (thickness : 20 mm)

---

additional exposition glass shelf

---

delivery overlay for the stainless steel panel front window

---

set of wheels (castors)

---

fans enforcing air circulation

---

additional LED light in top lamp profile

---

automatic defrost

---

the device with the temperature range from -2°C do +4°C (includes electric defroster heaters)

---

automatic condenser vaporization

---

electronic temperature recorder + software

---

